

TS 216 (600667000) Table saw
(220-240 V / 50 - 60 Hz); Cardboard box; with stand and trolley function

Order no. 600667000
EAN 4007430246851



Product may differ from image



- Lightest table saw with trolley function, also suitable for one-handed transport
- Integrated stand made from stable die-cast aluminium (patented): unfolded in a matter of seconds with secure stand
- Very compact with folded stand for comfortable transport and space-saving storage
- Second working height for working near ground level
- Anti-twist tubular frame construction for highest demands on the building site and during installations
- Cables and all add-on components for transport can be stored on the casing
- Powerful motor with electronic overload protection
- Motor brake for quick stop of the saw blade in 3 seconds
- Restart protection: prevents unintentional start-up after power supply interruption
- Soft start for long service life of motor and drive
- Precise rip fence with double clamping and quick fastening
- Precise saw blade inclination via gear guide
- Automatic resetting to 0 – 45 ° after undercuts
- Easy saw blade change with spindle lock
- Splitting wedge can be lowered without tools for hidden cuts and transport
- Precise, extendable table width extension for extra large working surfaces
- Dual port dust extraction for low dust emission

Technical data

Characteristics

Dimensions	670 x 730 x 355 mm // 2.2 x 2.4 x 2.1 ft
Max. support surface	780 x 930 mm // 30 1/2 x 36 1/2 "
Working height	850 / 355 mm // 33 1/2 / 14 "
Cutting height	0 - 63 mm // 0 - 2 1/2 "
Maximum cutting height 90/45°	63 / 43 mm // 2 1/2 / 1 11/16 "
Maximum cutting width at rip fence	425 mm / 16 3/4 "
Maximum material width at mitre fence	165 mm / 6 1/2 "
No-load speed	5000 rpm
Cutting speed	57 m/s / 187 ft/s
Saw blade	216 x 30 mm // 8 1/2 x 1.181 "
Saw blade swivel range	-1.5 - 46.5 °
Mains voltage	220 - 240 V
Rated input power	1500 W
Weight	28.5 kg / 62.8 lbs
Cable length	3 m / 10 ft

Noise emission

Sound pressure level	89 dB(A)
Sound power level (LwA)	102 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Carbide saw blade with alternately bevel-ground tips (30 teeth)
 Rip Fence
 Mitre Fence
 Table Length Extension
 Table width extension (left)
 Table width extension (right)
 Chip and Dust Extraction Unit
 Push stick
 Stand
 Hard rubber tyres