

Data sheet



Hot-melt glue applicator

GluePRO 300

Folding box

EAN 4007841035280



Function description

The new benchmark. The rugged GluePRO 300 with non-slip grip handle is comfortable to hold and has what it takes to become one of your favourite tools. This hot melt glue applicator is the key to convenient, reliable and tireless gluing work without compromising on anything. Practical stroke adjustment makes it possible to set the quantity of glue per stroke for any specific application. Warm-up time is approximately three minutes. Temperature: 190°C.

Technical specifications

Output, heat-up phase	300 W
Average power consumption	90 W
Temperature	190 – 190 °C
Melt temperature	190 – 190 °C
Temperature accuracy +/-	3 °C
Warm-up time	3
Delivery rate	25 gr/min
Max. stick diameter	11.7 mm
Function, hanger	Yes
Soft grip	Yes
Stroke adjustment	Yes
Idle mode	No
Dimensions (L x W x H)	283 x 83 x 212 mm
Nozzle can be changed	Yes
Mains power supply	220 – 230 V , 50 / 60 Hz
Model	Folding box
PU1, net weight	0,971 kg
Manufacturer's Warranty	1 year

Data sheet



Hot-melt glue applicator

GluePRO 300

Folding box

EAN 4007841035280

Technical specifications

PU1, EAN

4007841035280
