



Delock M.2 Docking Station for 2 x M.2 NVMe PCIe SSD with Clone function

Description

This M.2 docking station by Delock enables the installation of **two M.2 PCIe NVMe SSDs** and it can be connected via USB to the PC or laptop. The included USB cable allows the connection to a free USB-C™ port.

M.2 PCIe SSD clone function

The clone function enables to **copy the content of one SSD to another** without using a PC.

Good cooling

A **fan in the bottom area** of the docking station ensures sufficient cooling of the SSDs used, so that the operation also works without problems with closed lid.

Suitable as transport box

Due to the elegant design and the specially designed lid, the docking station is also suitable as a **transport box for two M.2 memories**.

CLONE
FUNCTION

M.2 NVMe



Specification

- Connectors:
 - 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female
 - 2 x 67 pin M.2 key M slot
 - 1 x DC jack
- Chipset: Asmedia ASM2362
- Supports M.2 modules with key M or key B+M based on PCIe (NVMe)
- Supports NVM Express (NVMe)
- Data transfer rate up to 10 Gbps
- Supports UASP
- LED indicator for power, access and copy status
- Function key:
 - 1 x Clone button
 - 1 x On / Off switch
- Dimensions (LxWxH): ca. 132 x 93 x 93 mm
- Hot Plug, Plug & Play

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.8 A
- Output: 12 V / 2 A
- Ground outside, plus inside
- Dimensions:
 - inside: ø ca. 2.5 mm
 - outside: ø ca. 5.5 mm
 - length: ca. 10 mm

System requirements

- Android 9.0 or above
- Chrome OS 83.0 or above
- iPad Pro (2018)
- Linux Kernel 5.4 or above
- Mac OS 10.15.6 or above
- Windows 8.1/8.1-64/10/10-64
- Device with a free USB Type-C™ port or with a free Thunderbolt™ 3 port

Package content

Item no. 63331

EAN: 4043619633319

Country of origin: China

Package: • Retail Box



- M.2 docking station
- Cable USB-C™ male to USB-C™ male, length ca. 1 m
- External power supply 12 V / 2 A
- User manual

Images





General	
Function:	Clone Function
Supported operating system:	Windows 8.1 32-bit
	Windows 8.1 64-bit
	Windows 10 32-bit
	Windows 10 64-bit
	iPad Pro (2018)
	Android 9.0 or above
	Chrome OS 83.0 or above
	Linux Kernel 5.4 or above
	Mac OS 10.15.6 or above
Slot:	PCIe
Maximum height of the components on the module:	1.5 mm application of double-sided assembled modules supported
Interface	
Connector 1:	1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female
Connector 2:	2 x 67 pin M.2 key M slot
connector 3:	1 x DC jack
Technical characteristics	
Data transfer rate:	10 Gbps
Physical characteristics	
Length:	132 mm
Width:	93 mm
Height:	93 mm
Colour:	white