



Delock Adapter USB 2.0 Type-A to 1 x Serial RS-232 DB9

Description

This USB 2.0 Type-A to serial adapter by Delock provides an RS-232 port for meters, POS systems, printers, modems, IoT devices, etc.

**1,8 m**

Specification

- Connectors:
 - 1 x USB 2.0 Type-A male >
 - 1 x serial RS-232 DB9 female with nuts
- Chipset: FTDI FT232
- Data transfer rate up to 921.6 Kbps
- Signals: Tx/D, Rx/D, RTS, CTS, DTR, DSR, DCD, RI, GND
- Parity: even, odd, none, mark, space
- Stop bits: 1, 2
- Databits: 7, 8
- Flow control: none, Xon / Xoff, RTS / CTS
- FIFO: 128 Byte - RX
- FIFO: 256 Byte - TX
- Cable length incl. connectors: ca. 1.8 m

System requirements

- Linux Kernel 2.6 or above
- Mac OS 10.9 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

Package content

- USB 2.0 to 1 x serial adapter
- Driver CD
- User manual

Item no. 66281


EAN: 4043619662814

Country of origin: China

Package: Retail Box



Images





General	
Function:	Plug & Play
Specification:	USB 1.1
	RS-232 (EIA / TIA)
	USB 2.0
Supported operating system:	Mac OS 10.9 or above
	Windows 7 32-bit
	Windows 7 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
	Windows 10 32-bit
	Windows 10 64-bit
	Linux Kernel 2.6 or above
Interface	
Connector 1:	1 x USB 2.0 Type-A male
Connector 2:	1 x Serial RS-232 DB9 female
Technical characteristics	
Chipset:	FTDI 232R
Data transfer rate:	up to 921.6 Kbps
FIFO:	128 byte
	256 Byte
Data transmission:	asynchronous
	Bi-directional
UART:	USB to serial UART
Physical characteristics	
Cable length:	1.8 m
Pin finishing:	gold-plated
Shielding:	double
Colour:	black