



Delock Cable mini Displayport 1.2 male with screw > DVI male 4K 30 Hz Active 5 m black

Description

This cable by Delock allows the connection of a DVI display via a mini Displayport interface. It supports a resolution of up to Ultra HD (4K) and is backwards compatible to Full-HD 1080p. The screw of the mini Displayport connector secures the connection and prevents accidental unplugging of the cable.



ca. 5 m

Specification

- Connectors:
 - 1 x mini Displayport 20 pin male with screw >
 - 1 x DVI 24+1 male with screws
- DVI-D (Single Link), VGA not wired
- Input = mini Displayport; Output = DVI
- Screw type: #4-40, thread type UNC, thread class 3A, American Standard Screw
- Chipset: Parade PS176
- Displayport 1.2 specification
- Cable gauge: 32 AWG
- Cable diameter: ca. 5.5 mm
- Gold-plated connectors
- Active cable, for graphics cards with DP and DP++ output
- Resolution up to 2560 x 1600 @ 60 Hz / 3840 x 2160 @ 30 Hz / 4096 x 2160 @ 24 Hz (depending on the system and the connected hardware)
- Supports HDCP 1.3
- Supports Eyefinity
- 2 x ferrite core
- Length incl. connectors (L): ca. 5 m
- Colour: black
- OS independent, no driver installation necessary

System requirements

- One free mini Displayport female

Package content


- Cable mini Displayport to DVI

Item no. 85637

EAN: 4043619856374

Country of origin: China

Package: Poly bag





General	
Specification:	Displayport 1.2 HDCP 1.3
Interface	
connector 1:	1 x mini Displayport 20 pin male
connector 2:	1 x DVI 24+1 male with screws
Technical characteristics	
Chipset:	Parade PS176
Maximum screen resolution:	3840 x 2160 @ 30 Hz 4096 x 2160 @ 24 Hz
Physical characteristics	
Ferrite core:	2 x
Cable diameter:	5.5 mm
Pin finishing:	gold-plated
Conductor gauge:	32 AWG
Screw type:	#4-40 UNC
Length:	5 m
Colour:	black