

Technical Specifications

APC Netshelter Rack Automatic Transfer Switch, 2U, 32A, 230V, 2 IEC 309 IN, 16 C13, 2 C19 OUT, 50/60 Hz | AP4424A | Downloaded on 11/02/2022 (EST)

Life Is On



APC Netshelter Rack Automatic Transfer Switch, 2U, 32A, 230V, 2 IEC 309 IN, 16 C13, 2 C19 OUT, 50/60 Hz

AP4424A

Call for More Information 0800 2799254

- Includes: Mounting hardware, Rack mounting brackets, Serial configuration cable

Output	
Always on Outlets	18
Overload Protection	Yes
Maximum Total Current Draw	32

Input	
Input frequency	50/60 Hz
Input Connections	IEC 60320, IEC 60320 IEC 60309 32 A 2P + E
Cord Length	2.4meters
Acceptable Input Voltage	207 - 253VAC
Number of Power Cords	2
Load Capacity	7400VA

Physical	
Maximum Height	88MM, 8.8CM
Maximum Width	432MM, 43.2CM
Maximum Depth	236MM, 23.6CM
Rack Height	2U
Net Weight	6.94KG
Color	Black

Environmental	
Operating Temperature	-5 - 45 °C

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Netshelter Rack Automatic Transfer Switch, 2U, 32A, 230V, 2 IEC 309 IN, 16 C13, 2 C19 OUT, 50/60 Hz | AP4424A | Downloaded on 11/02/2022 (EST)



Environmental	
Operating Relative Humidity	5 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %

Conformance	
Approvals	EN 55022 class A, FCC part 15 class A
Standard warranty	2 years repair or replace

Sustainable Offer Status	
RoHS	Compliant
Other Environmental Compliance	China RoHS

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.