

AXIS I/O Indication LED

Clean and simple design

AXIS I/O Indication LED lets you easily see if the camera is active or not, for instance when there is concern for privacy or when you want to deter antisocial and criminal behavior. The sleek, simple design of AXIS I/O Indication LED makes it ideal for surveillance within retail, transport and healthcare environments. Quick to install with an adhesive strip, and using only one cable to connect to the I/O port of the camera. Easy to setup and configure within the camera's settings.

- > **Notify when recording**
- > **Active on motion detection**
- > **Quick and easy to install**



AXIS I/O Indication LED

General		Approvals	Environment
Casing	Plastic casing IP44-rated Color: white NCS S 1002-B		EN 50581, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC/EN 60529 IP44
Sustainability	PVC free	Dimensions	Height: 11 mm (0.43 in) Width: 14 mm (0.55 in) 400 mm (15.7 in) cable
Power	Input voltage: 12 V DC (Powered by device via I/O connector) Current required: 15 mA	Weight	8 g (0.018 lb)
Operating conditions	-20 °C to 70 °C (-4 °F to 158 °F) Humidity 00-100% RH (non-condensing)	Warranty	3-year warranty, see axis.com/warranty
Storage conditions	-40 °C to 70 °C (-40 °F to 158 °F)	Environmental responsibility: axis.com/environmental-responsibility	