



APC Smart-UPS C, Line Interactive, 1500VA, Rackmount 2U, 230V, 4x IEC C13 outlets, SmartConnect port, USB and Serial communication, AVR, Graphic LCD



Brand : APC

Product code: SMC1500I-2UC

Product name : Smart-UPS C, Line Interactive, 1500VA, Rackmount 2U, 230V, 4x IEC C13 outlets, SmartConnect port, USB and Serial communication, AVR, Graphic LCD

- 1500VA/900W line interactive pure sine wave 2U rackmount UPS
 - Ideal for entry-level servers, networks, retail POS, and business VOIP
 - Automatic Voltage Regulation keeps output voltage within acceptable user selectable levels
 - Cloud-based remote power monitoring via SmartConnect Ethernet Port
 - Graceful shutdown using serial or USB cables via PowerChute Serial Shutdown
- Smart-UPS C, Line Interactive, 1500VA, Rackmount 2U, 230V, 4x IEC C13 outlets, SmartConnect port, USB and Serial communication, AVR, Graphic LCD

Features		Battery	
UPS topology *	Line-Interactive	Cold start	✓
Output power capacity *	1.5 kVA	Design	
Output power *	900 W	Form factor *	Rackmount
Waveform *	Sine	Rack capacity	2U
Input operation voltage (min) *	170 V	Product colour *	Black
Input operation voltage (max) *	300 V	Display type	LCD
Input frequency *	50/60 Hz	LED indicators	✓
Output operation voltage (min)	220 V	Operational conditions	
Output operation voltage (max)	240 V	Operating temperature (T-T)	0 - 40 °C
Output frequency	50/60 Hz	Storage temperature (T-T)	-15 - 45 °C
Automatic Voltage Regulation (AVR)	✓	Operating relative humidity (H-H)	0 - 95%
Surge energy rating	459 J	Storage relative humidity (H-H)	0 - 95%
Output voltage Total Harmonic Distortion (THD)	5%	Operating altitude	0 - 3000 m
Noise level	46 dB	Non-operating altitude	0 - 15000 m
Audible alarm(s)	✓	Certificates	
Web-based management	✓	Certification	C-tick, CE, CSA, GOST, UL 1778, VDE
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm	Packaging content	
Auto-restart	✓	Rack mount kit	✓
Temperature voltage compensation	✓	Cables included	USB cable
Ports & interfaces		Management card included	✗
AC outlet types	C13 coupler	Quick installation guide	✓
Power plug	C14 coupler	Sustainability	
AC outlets quantity	4 AC outlet(s)	Sustainability certificates	Green Premium
USB port	✓	Weight & dimensions	
USB 2.0 ports quantity	1	Width	432 mm
Serial interface	✓	Depth	477 mm
Serial interface type	RJ-45	Height	86 mm
SmartSlot	✗	Weight	28.6 kg
SmartConnect port	✓	Packaging data	
Battery		Resource CD	✓
Battery technology	Sealed Lead Acid (VRLA)	Software CD	✓
Battery life (max)	6 year(s)	Package width	594 mm
Battery recharge time	3 h	Package depth	603 mm
Hot-swap battery	✓	Package height	251 mm
Automatic battery test	✓		

Packaging data	
Package weight	31.9 kg
Logistics data	
Products per pallet	16 pc(s)
Harmonized System (HS) code	85078000
Total carbon footprint (kg of CO2e)	1363.77



0731304332954



731304332954

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.