



APC Smart-UPS SMT3000IC - 8x C13, 1x C19, USB, SmartConnect, 3000VA

Brand : APC

Product code: SMT3000IC

Product name : APC Smart-UPS SMT3000IC - 8x C13, 1x C19, USB, SmartConnect, 3000VA

- Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices

- Includes: CD with software, Documentation CD, USB cable

APC Smart-UPS SMT3000IC - 8x C13, 1x C19, USB, SmartConnect, 3000VA

APC Smart-UPS SMT3000IC - 8x C13, 1x C19, USB, SmartConnect, 3000VA. UPS topology: Line-Interactive, Output power capacity: 3 kVA, Output power: 2700 W. AC outlet types: C13 coupler, C19 coupler, Power plug: C20 coupler, AC outlets quantity: 9 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 5.1 min, Typical backup time at half load: 17.2 min. Form factor: Tower, Product colour: Black, Cable length: 1.83 m. Compliance certificates: RoHS, Certification: CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE, REACH, PEP, EOL




Features		Battery	
UPS topology *	Line-Interactive	Cold start	✓
Output power capacity *	3 kVA	Design	
Output power *	2700 W	Form factor *	Tower
Waveform *	Sine	Cable length	1.83 m
Input operation voltage (min) *	151 V	Product colour *	Black
Input operation voltage (max) *	302 V	Display type	LCD
Input frequency *	50/60 Hz	LED indicators	Status
Output operation voltage (min)	220 V	Operational conditions	
Output operation voltage (max)	240 V	Operating temperature (T-T)	0 - 40 °C
Output frequency	50/60 Hz	Storage temperature (T-T)	-15 - 45 °C
Automatic Voltage Regulation (AVR)	✓	Operating relative humidity (H-H)	0 - 95%
Surge energy rating	365 J	Storage relative humidity (H-H)	0 - 95%
Efficiency	98.4%	Operating altitude	0 - 3000 m
Emergency Power Off (EPO)	✓	Non-operating altitude	0 - 15000 m
Noise level	53 dB	Certificates	
Audible alarm(s)	✓	Compliance certificates	RoHS
Auto-restart	✓	Certification	CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE, REACH, PEP, EOL
Ports & interfaces		Packaging content	
AC outlet types	C13 coupler, C19 coupler	Cables included	RS-232, USB cable
Power plug	C20 coupler	Management card included	✗
AC outlets quantity	9 AC outlet(s)	Quick installation guide	✓
Number of output IEC jumpers	2	Sustainability	
USB port	✓	Sustainability certificates	Green Premium
SmartSlot	✓		
SmartConnect port	✓		
Battery			
Battery technology	Sealed Lead Acid (VRLA)		

Battery		Weight & dimensions	
Typical backup time at full load	5.1 min	Width	197 mm
Typical backup time at half load	17.2 min	Depth	544 mm
Battery life (max)	5 year(s)	Height	435 mm
Battery recharge time	3 h	Weight	52.5 kg
Hot-swap battery	✓	Packaging data	
Automatic battery test	✓	Package width	381 mm
		Package depth	762 mm
		Package height	699 mm
		Package weight	63.7 kg
		Logistics data	
		Products per pallet	9 pc(s)
		Harmonized System (HS) code	85078000
		Total carbon footprint (kg of CO2e)	3335.07



0731304337331



731304337331



5706998577092

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.