




Gamer Storm PN750M power supply unit 750 W 20+4 pin ATX ATX Black

Brand : Gamer Storm

Product code: R-PN750M-FC0B-JGEU

Product name : PN750M

750W, ATX12V V3.1, FDB, APFC, 120 mm, 20+4 Pin, 2x CPU(4+4)Pin, 3x PCI-E 6+2 Pin, 8x SATA, 12V-2x6(16Pin), 150 × 140 × 86 mm, Black, EU
Gamer Storm PN750M. Total power: 750 W, AC input voltage: 100 - 240 V, AC input frequency: 50/60 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 55 cm, SATA power cable length: 450,570,690,810 mm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Gold. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Cables included: AC, CPU, PCIe, Peripheral (Molex), SATA



Power		Ports & interfaces	
Total power *	750 W	CPU power connector (4+4 pin)	✓
AC input voltage *	100 - 240 V	CPU power cable length	70 cm
AC input frequency	50/60 Hz	ATX power connector (20+4 pin)	✓
Input current	10 - 5 A	Cabling type	Fully-Modular
Power Factor Correction (PFC) type	Active	Performance	
Combined power (+3.3V)	110 W	80 PLUS certification *	80 PLUS Gold
Combined power (+12V)	750 W	Purpose *	PC
Combined power (+5V)	110 W	Power supply unit (PSU) form factor	ATX
Combined power (-12V)	3.6 W	*	
Combined power (+5Vsb)	15 W	ATX version	3.1
Max output current (+3.3V)	20 A	Bearing technology	FDB
Max output current (+12V)	62.5 A	Mean time between failures (MTBF)	100000 h
Max output current (+5V)	20 A	Design	
Max output current (-12V)	0.3 A	Product colour	Black
Max output current (+5Vsb)	3 A	Cooling type	Active
Hold time	16 ms	Fan diameter	12 cm
Efficiency	90%	Number of fans	1 fan(s)
Power Good signal delay range	100 - 150 ms	Fan location	Top
Power protection features	No load operation, Over power, Over voltage, Overheating, Short circuit, Surge & inrush protection (SIP), Surge protection, Under voltage	On/off switch	✓
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
Ports & interfaces		Packaging content	
Motherboard power connector *	20+4 pin ATX	Cables included	AC, CPU, PCIe, Peripheral (Molex), SATA
Motherboard power cable length	55 cm	Cable tie(s) included	✓
Number of SATA power connectors	8		
SATA power cable length	450,570,690,810 mm		
Peripheral (Molex) power connectors (4-pin) *	2		

Ports & interfaces		Certificates	
Peripheral (Molex) power cable length	930 mm	Compliance certificates	CCC, CE, EAC, Federal Communications Commission (FCC), RCM, RoHS, WEEE
PCI Express power connectors (6+2 pin)	3	Weight & dimensions	
PCI Express power connectors (16-pin)	1	Width	150 mm
		Depth	140 mm
		Height	86 mm
		Packaging data	
		Package type	Box
		Technical details	
		Sustainability certificates	ErP, Triman
		Logistics data	
		Warranty period	10 year(s)



6933412740889

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.