



FSP HYPER 80+ PRO 550W Power supply unit ATX ATX3.1 Black

Brand : FSP

Product code: 9PA5509407

Product name : HYPER 80+ PRO 550W Power supply unit ATX ATX3.1 Black

- Complies with ATX12 V2.4 & EPS12 V2.92
- Efficiency $\geq 88\%$ at typical load
- Active PFC ≥ 0.9
- Hold up time > 17ms at 80% load
- 450V, 105°C capacitors for a long product life cycle
- +12V single-rail design
- +5V & 3.3V DC to DC module design
- 120mm silent and long life fan
- All black round cables
- Complete protection: OCP/OVP/OPP/SCP

HYPER 80+ PRO 550W, ATX, 120mm Sleeve Fan, 80 Plus Bronze

FSP HYPER 80+ PRO 550W Power supply unit ATX ATX3.1 Black. Total power: 550 W, AC input voltage: 200 - 240 V, Input current: 4.5 A. Motherboard power connector: 24-pin ATX, Cabling type: Non-Modular. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Bronze. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Certification: IEC 62368



Power		Ports & interfaces	
Total power *	550 W	PCI Express power connectors (6+2 pin)	2
AC input voltage *	200 - 240 V	Floppy drive power connector	1
Input current	4.5 A	Floppy disk drive connector	✓
Power factor	0.9	Cabling type	Non-Modular
Power Factor Correction (PFC) type	Active	Performance	
Combined power (+3.3V)	85 W	80 PLUS certification *	80 PLUS Bronze
Combined power (+12V)	549.6 W	Purpose *	PC
Combined power (+5V)	85 W	Power supply unit (PSU) form factor *	ATX
Combined power (-12V)	3.6 W	ATX version	2.4
Combined power (+5Vsb)	12.5 W	EPS version	2.92
Max output current (+3.3V)	16 A	Design	
Max output current (+12V)	45.8 A	Product colour	Black
Max output current (+5V)	16 A	Cooling type	Active
Max output current (-12V)	0.3 A	Fan diameter	12 cm
Max output current (+5Vsb)	2.5 A	Number of fans	1 fan(s)
Hold time	17 ms	Illumination	✗
Efficiency	85%	Certificates	
Power protection features	Over current, Over power, Over voltage, Short circuit	Certification	IEC 62368
Ports & interfaces		Weight & dimensions	
Motherboard power connector *	24-pin ATX	Width	150 mm
Number of SATA power connectors	5	Depth	140 mm
Peripheral (Molex) power connectors (4-pin) *	2	Height	86 mm
EPS power connector (4+4 pin)	✓	Weight	1.25 kg
Technical details			
Sustainability compliance		✓	
Sustainability certificates		ErP	



4711498480569

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.