




LevelOne 6-Port Gigabit PoE Industrial Switch, 802.3at/af PoE, 4 PoE Outputs, 1 x SFP, 1 x SFP/RJ45 Combo, -40°C to 75°C, DIN-Rail, 126W

Brand : LevelOne

Product code: IES-0610

Product name : 6-Port Gigabit PoE Industrial Switch, 802.3at/af PoE, 4 PoE Outputs, 1 x SFP, 1 x SFP/RJ45 Combo, -40°C to 75°C, DIN-Rail, 126W

4x PoE 10/100/1000Base-T, 1x Gigabit Combo RJ45/SFP, 1x 100/1000Base-X SFP, 1024 MAC, 12Gbps LevelOne 6-Port Gigabit PoE Industrial Switch, 802.3at/af PoE, 4 PoE Outputs, 1 x SFP, 1 x SFP/RJ45 Combo, -40°C to 75°C, DIN-Rail, 126W. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 4. Full duplex. MAC address table: 1024 entries, Switching capacity: 12 Gbit/s. Networking standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z. Power over Ethernet (PoE). Wall mountable



Ports & interfaces		Power over Ethernet (PoE)	
Basic switching RJ-45 Ethernet ports quantity *	4	Power over Ethernet plus (PoE+) ports quantity	4
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power over Ethernet (PoE) power per port	30 W
Combo SFP ports quantity	1	Total Power over Ethernet (PoE) budget	126 W
SFP module slots quantity	1	Other features	
Network		Terminal block port	✓
Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Operational conditions	
10G support *	✗	Operating temperature (T-T)	-40 - 75 °C
Full duplex	✓	Storage temperature (T-T)	-40 - 85 °C
Flow control support	✓	Operating relative humidity (H-H)	5 - 95%
Auto MDI/MDI-X	✓	Storage relative humidity (H-H)	5 - 95%
Auto-negotiation	✓	Weight & dimensions	
Data transmission		Width	40 mm
Switching capacity *	12 Gbit/s	Depth	105 mm
MAC address table *	1024 entries	Height	38 mm
Store-and-forward	✓	Weight	720 g
Jumbo frames	10000	Packaging content	
Packet forwarding rate (1 Gbps)	148800 pps	Quick start guide	✓
Packet forwarding rate (100 Mbps)	148000 pps	Packaging data	
Packet forwarding rate (10 Mbps)	14880 pps	Package type	Box
Packet buffer memory	1 MB	Package width	215 mm
Design		Package depth	165 mm
Product colour	Black	Package height	65 mm
LED indicators	Activity, Link, Power	Package weight	120 g
Wall mountable	✓	Certificates	
DIN rail mounting	✓	Certification	
Power		FCC Part 15 Subpart B Class A CE EN 55022 Class A EN61000-4-2 (ESD) Level 3 EN61000-4-3 (RS) Level 3 EN61000-4-4 (EFT) Level 3 EN61000-4-5 (Surge) Level 3 EN61000-4-6 (CS) Level 3 EN61000-4-8 (Magnetic Field) Level 3 UL508 (Pending) EN 50121-4 (Pending) IEC 60068-2-27 IEC 60068-2-32 IEC 60068-2-6 UL 508	
Input voltage	48 - 55 V		
Power consumption (typical)	6 W		
Power protection features	Overload, Reverse polarity		

Power over Ethernet (PoE)		Logistics data	
Power over Ethernet (PoE) *	✓	Country of origin	Taiwan
		Harmonized System (HS) code	85176990



4015867188507

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.