



DELL 407-BBXU network transceiver module Fiber optic 25000 Mbit/s SFP28 850 nm



Brand : DELL

Product code: 407-BBXU

Product name : 407-BBXU

25GbE SFP28, SR, LC, MMF

DELL 407-BBXU network transceiver module Fiber optic 25000 Mbit/s SFP28 850 nm:

The Dell™ SFP28 transceiver delivers fiber connectivity to extend the range of your network. This hot-pluggable transceiver with SFP28 (Small Form Factor Pluggable) footprint features a Duplex LC connector. The Dell networking 25GbE-MMF SFP28 transceiver provides 25GbE connectivity up to 300m.

Additionally, it provides a unique enhanced digital diagnostic monitoring interface, which allows real-time access to device operating parameters such as transceiver temperature, laser bias current, transmitted optical power, received optical power, and transceiver supply voltage.

DELL 407-BBXU. SFP transceiver type: Fiber optic, Maximum data transfer rate: 25000 Mbit/s, Interface type: SFP28. Brand compatibility: Dell, Compatible products: - Networking S5212F-ON - Networking S5224F-ON - Networking S5232F-ON - Networking S5248F-ON - Quantity per pack: 1 pc(s)

Performance		Features	
SFP transceiver type *	Fiber optic	Hot-Plug support	✓
Maximum data transfer rate *	25000 Mbit/s	Brand compatibility	Dell
Interface type *	SFP28	Compatible products	- Networking S5212F-ON - Networking S5224F-ON - Networking S5232F-ON - Networking S5248F-ON - Networking S5296F-ON - PowerEdge C4140 - PowerEdge C6420 - PowerEdge FC640 - PowerEdge M640 - PowerEdge M640 VRTX - PowerEdge R440 - PowerEdge R540 - PowerEdge R640 - PowerEdge R6415 - PowerEdge R740 - PowerEdge R740XD - PowerEdge R740xd2 - PowerEdge R7415 - PowerEdge R7425 - PowerEdge R840 - PowerEdge R940 - PowerEdge R940xa - PowerEdge T440 - PowerEdge T640
Single-mode fiber (SMF) supported	✗		
Multi-mode fiber (MMF) supported	✓		
Fiber optic connector	LC		
SFP transceiver standard	SR		
Maximum transfer distance	300 m		
Wavelength	850 nm		
Ethernet interface type	25 Gigabit Ethernet		
Packaging content			
Quantity per pack	1 pc(s)		
Logistics data			
Harmonized System (HS) code	85369010		



5397184377109



0884116381815



884116381815

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.