

Vivolink VLHDMIMAT4X2RS matrix switcher Scaling matrix switcher 7.5 W


Brand : Vivolink

Product code: VLHDMIMAT4X2RS

Product name : VLHDMIMAT4X2RS



- 4x2 HDMI presentation switcher with matrix outputs
 - HDMI 2.0b, 4K@60Hz 4:4:4 8bit, HDR 10, HDCP 2.2
 - RS232, IR and WEB GUI control (not telnet)
 - 4K to 1080p down-scaling
 - SPDIF and 3.5mm output for dual HDMI OUT audio extraction and dual HDMI OUT ARC
 - Smart EDID management
 - True 4K matrix switcher that can be controlled via WEB GUI
- HDMI 2.0 4x2, 4K@60Hz, 18Gbps, HDCP 2.2, SPDIF, 3.5mm, RS-232, 200x28.5x100 mm



Vivolink VLHDMIMAT4X2RS matrix switcher Scaling matrix switcher 7.5 W:

VLHDMIMAT4X2RS is a 4K HDR capable 4x2 HDMI Matrix Switcher that features 18Gbps bandwidth and HDCP2.2 on all inputs and outputs. It's fully compliant with HDMI2.0 standard and backward compatible with old HDMI1.4 sources and displays. SPDIF and 3.5mm audio breakout audio from corresponding HDMI outputs.

Smart EDID management.

True 4K matrix switcher that can be controlled via WEB GUI (not telnet)

Features		Ports & interfaces	
Product type *	Scaling matrix switcher	Ethernet LAN (RJ-45) ports	1
Maximum resolution	3840 x 2160 pixels	RS-232 ports	1
Bandwidth	18 Gbit/s	Audio (L/R) out	1
HDCP	✓	Power	
HDCP version	2.2	Power consumption (max) *	7.5 W
High Dynamic Range (HDR) supported	✓	AC input voltage	100 - 240 V
Extended display identification data (EDID)	✓	AC input frequency	50 - 60 Hz
Audio formats supported	PCM	Output current	1000 mA
Design		Output voltage	12 V
Housing colour	Black	Operational conditions	
Control type	Buttons	Operating temperature (T-T)	-5 - 55 °C
LED indicators	✓	Logistics data	
Remote control included	✓	Harmonized System (HS) code	85299097
Display		Weight & dimensions	
Built-in display *	✗	Width	200 mm
Ports & interfaces		Depth	100 mm
HDMI input ports quantity	4	Height	28.5 mm
HDMI output ports quantity	2	Weight	860 g
HDMI version	2.0b	Package width	264 mm
RJ-45 input ports	1	Package depth	233 mm
Digital audio optical out	1	Package height	84 mm
USB connector type	Micro-USB	Package weight	1.05 kg
USB ports quantity	1	Packaging content	
		Cables included	IR sensor
		Mounting brackets included	✗
		AC adapter included	✓



5706998972637

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.