

Vivolink VL120016R AV extender AV receiver Black

Brand : Vivolink

Product code: VL120016R

Product name : VL120016R

- Support up to 4K@60Hz 4:2:0 video signal transmission
 - Max transmission distance is 4K 131ft (40m) and 1080P 230ft (70m) over single CAT5e/CAT6 cable
 - High Bandwidth: 10.2Gbps
 - Compliant with HDMI & HDCP1.4
 - Use HDBaseT technology for extended capability and reliability
 - Support ARC
 - Bi-directional IR pass-through
- HDMI Extender slim 4K with IR + RS-232 control, Receiver, 70m

Input	1 x HDMI (female), 1 x IR (3.5 mini jack), 1 x RS232 (3pin captive screw connector)
Output	1 x HDBT (RJ45), 1 x IR (3.5 mini jack), 1 x RS232 (3pin captive screw connector)
Input	1 x HDBT (RJ45), 1 x IR (3.5 mini jack), 1 x RS232 (3pin captive screw connector)
Output	1 x HDMI (female), 1 x IR (3.5 mini jack), 1 x RS232 (3pin captive screw connector)
Signal Standard	HDMI 1.4 & HDCP 2.2
Audio	Digital Audio, Audio transmitted through HDMI
Transmission Distance	1080Ps70m, 4Kx2Ks40m
Temperature	0~ 50°C
Reference Humidity	10% ~ 90%
Power Supply	Input: 100VAC~240VAC, 50/60Hz Output: DC 24V, 1.25A /
Dimension (W*H*D)	W115xH16.2x D84mm
Power Consumption	11W
Weight	0.15Kg (Tx) / 0.15Kg (Rx)

Vivolink VL120016R AV extender AV receiver Black:

VL120016R is a mini-size HDBaseT Extender receiver, supporting 1080P/ 4K signal transmission up to 131ft (40m), 1080P signal up to 230ft (70m) over single CAT5e/6 cable. VL120016 supports CEC, bidirectional RS232 & IR control, and one way-directional PoH function.

Note:

Not compatible with HDBaseT splitter VLHDBSP1X4V2

Features		Ports & interfaces	
Type *	AV receiver	Remote (IR) input	1
Cable types supported	Cat5e	Remote (IR) output	1
Maximum transfer distance	70 m	DC-in jack	✓
IR pass-through	✓	Power	
HDCP pass-through	✓	AC input voltage	100 - 240 V
RS-232 pass-through	✓	AC input frequency	50 - 60 Hz
CEC pass-through	✓	Operating voltage	24 V
LED indicators	✓	Output current	1.25 A
Supported video modes	3840p	Power consumption (receiver) (max)	11 W
Bandwidth	10.2 Gbit/s	External power adapter	✓
Remote control type	IR + RS232	Power over Ethernet (PoE)	✓
HDCP	✓	Operational conditions	
3D	✓	Operating temperature (T-T)	-20 - 70 °C
HDCP & EDID bypass	✓	Operating relative humidity (H-H)	10 - 90%
Consumer Electronics Control (CEC) support	✓	Weight & dimensions	
Wall mountable	✓	Width	115 mm
HDCP version	2.2	Depth	84 mm
Product colour	Black	Height	16.2 mm
HDBaseT certified	✓	Weight	208 g
Ports & interfaces		Packaging data	
Connectivity technology *	Wired	Package width	152 mm
RJ-45 input ports	1	Package depth	151 mm
HDMI in	1	Package height	81 mm
Number of HDMI outputs	1	Package weight	308 g
HDMI version	1.4	Packaging content	
RS-232 input ports	1	AC adapter included	✓
RS-232 output ports	1	Included power plug types	EU
Video in	1	IR blaster included	✗
Video out	1	IR receiver included	✗
Serial ports quantity	1	Mounting brackets included	✓
Serial interface type	RS-232	Technical details	
3.5 mm (1/8-inch) in	✓	Audio support	✓
3.5 mm (1/8-inch) out	✓		



5711783613282

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.