


Viewsonic 65" 4K Professional Commercial Display with ProAV Integration



Brand : Viewsonic

Product code: CDE6531-1C

Product name : 65" 4K Professional Commercial Display with ProAV Integration

- Fast Warm Boot eliminates long startup delays, launching signage and content in under 7 seconds.
 - Native 4K UHD in Any Orientation delivers sharp, high-resolution visuals in landscape or portrait.
 - USB media playback & scheduling with automatic failover ensures uninterrupted signage
 - Commercial-Grade Brightness & 24/7 Reliability keep content clear and visible around the clock.
 - Centralized control with Pro-AV integration and remote management via Web UI and ViewSonic Manager.
 - Secure, Future-Ready Platform with Android 14, upgradeable OS, Quad-Core SoC, and 8 GB RAM.
- 65", 4K UHD (3840 x 2160), TFT LCD, DLED, 500 nits, 2000:1, 6.5 ms, Quad-core ARM Cortex-A73, 8GB, 32GB, 2x 16 W, HDMI 2.0/2.1, RS-232, WIFI slot, SPDIF, RJ45, USB-A, USB-C, 3.5 mm, Android 14 AOSP

Display		Design	
Panel type	TFT	Bezel width (side)	1.59 cm
LED backlight	✓	Bezel width (top)	1.59 cm
LED backlighting type	Direct-LED	Anti-glare screen	✓
Display diagonal *	165.1 cm (65")	Performance	
Display technology *	LCD	Purpose *	Commercial
Display resolution *	3840 x 2160 pixels	Operating hours (hours/days)	24/7
Display brightness *	500 cd/m²	Power	
HD type *	4K Ultra HD	Power consumption (typical) *	74.23 W
Touchscreen *	✗	Energy efficiency class (SDR)	F
Native aspect ratio	16:9	AC input voltage	100 - 240 V
Response time	6.5 ms	Computer system	
Contrast ratio (typical)	1200:1	Built-in processor *	✓
Contrast ratio (dynamic)	5000:1	Processor manufacturer	ARM
Viewing angle, horizontal	178°	Processor architecture	ARM Cortex-A73
Viewing angle, vertical	178°	Processor cores	4
Active display area (W x H)	1428.48 x 803.52 mm	Internal memory	8 GB
Panel life	50000 h	Internal storage capacity	32 GB
Native refresh rate	60 Hz	Operating system installed	Android 14
Haze rate	25%	Weight & dimensions	
Surface hardness	3H	Display width	1463.3 mm
Ports & interfaces		Display depth	68 mm
HDMI ports quantity *	4	Display height	806.5 mm
HDMI version	2.0/2.1	Display weight	23.9 kg
HDMI input ports quantity	3	Weight	23.9 kg
HDMI output ports quantity	1	Packaging data	
DVI port *	✗	Package width	1628 mm
DisplayPort version	1.2	Package depth	185 mm
USB port *	✓	Package height	942 mm
USB ports quantity	3	Package weight	32.2 kg
USB version	2.0/3.2 Gen 1 (3.1 Gen 1)	Packaging content	
USB connector type	USB Type-A, USB Type-C	Remote control included	✓
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1	Batteries included	✓
USB Power Delivery (USB PD)	✓	Cables included	AC, HDMI, RS-232
USB Power Delivery up to	65 W	Mounting kit	✓
USB Type-C DisplayPort Alternate Mode	✓	Operational conditions	
Ethernet LAN (RJ-45) ports	2	Operating temperature (T-T)	0 - 40 °C
PC Audio in	✓		

Ports & interfaces		Operational conditions	
RS-232 interface	✓	Operating relative humidity (H-H)	20 - 80%
Digital audio optical out	1	Logistics data	
PC Audio out	✓	Products per master (outer) case	1 pc(s)
OPS module slot	✓	Pallet gross length	114 cm
Audio		Pallet gross width	168 cm
Built-in speaker(s) *	✓	Pallet gross height	107.2 cm
Number of built-in speakers	2	Harmonized System (HS) code	8528521000
RMS rated power	32 W	Network	
Design		Ethernet LAN *	✓
Product design *	Digital signage flat panel	Ethernet LAN data rates	10,100,1000 Mbit/s
Placement supported *	Indoor	Wi-Fi *	✓
Orientation	Horizontal/Vertical	Technical details	
Product colour *	Black	OPS slot	1
Screen shape	Flat	Sustainability certificates	ENERGY STAR, EPEAT Gold, ErP
VESA mounting *	✓	Compliance certificates	CB, CE, EAC, Federal Communications Commission (FCC), RCM, REACH, RoHS, WEEE, cTUVus
Panel mounting interface	600 x 400 mm	Other features	
Bezel width (bottom)	1.59 cm	Bundled software	AirSync, Manager



766907034721

Catalog Object Cloud