



## FSP Twins PRO 900W Power supply unit PS2 ATX Redundant ATX Black

**Brand :** FSP

**Product code:** PPA9000600

**Product name :** Twins PRO 900W Power supply unit PS2 ATX Redundant ATX Black

- FSP900-50REB
- ATX PS2 redundant size
- Efficiency  $\geq 90\%$  at typical load
- Quiet and long-lasting 40mm ball bearing fan
- Ribbon cables for th need of enthusiasts
- Powerful single +12V rail design
- All Japanese electrolytic capacitors
- Intel Latest CPU ready
- Full protections OCP, OVP, SCP, OPP, OTP, FFP, UVP

900W, PS2 ATX Redundant, 2x 40mm, 20+4-pin, 4+4-pin, 2x PCIe 6+2-pin, 6x SATA, 1x Molex, 80 PLUS Gold

FSP Twins PRO 900W Power supply unit PS2 ATX Redundant ATX Black. Total power: 900 W, AC input voltage: 100 - 240 V, AC input frequency: 50 - 60 Hz. Motherboard power connector: 20+4 pin ATX, Cabling type: Non-Modular. Purpose: Server, Power supply unit (PSU) form factor: PS/2, 80 PLUS certification: 80 PLUS Gold. Product colour: Black, Fan diameter: 4 cm, Number of fans: 2 fan(s). Cables included: CPU, PCIe, SATA



| Power                                         |                                                                                   | Ports & interfaces                     |                 |
|-----------------------------------------------|-----------------------------------------------------------------------------------|----------------------------------------|-----------------|
| Total power *                                 | 900 W                                                                             | PCI Express power connectors (6+2 pin) | 4               |
| AC input voltage *                            | 100 - 240 V                                                                       | CPU power connector (4+4 pin)          | ✓               |
| AC input frequency                            | 50 - 60 Hz                                                                        | Cabling type                           | Non-Modular     |
| Input current                                 | 6 - 10 A                                                                          | Performance                            |                 |
| Power Factor Correction (PFC) type            | Active                                                                            | 80 PLUS certification *                | 80 PLUS Gold    |
| Combined power (+3.3V)                        | 130 W                                                                             | Purpose *                              | Server          |
| Combined power (+5V)                          | 130 W                                                                             | Power supply unit (PSU) form factor *  | PS/2            |
| Max output current (+3.3V)                    | 20 A                                                                              | Bearing technology                     | DBB             |
| Max output current (+12V)                     | 75 A                                                                              | Design                                 |                 |
| Max output current (+5V)                      | 20 A                                                                              | Product colour                         | Black           |
| Max output current (-12V)                     | 0.5 A                                                                             | Fan diameter                           | 4 cm            |
| Max output current (+5Vsb)                    | 3 A                                                                               | Number of fans                         | 2 fan(s)        |
| Efficiency                                    | 90%                                                                               | Packaging content                      |                 |
| Power protection features                     | Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage | Cables included                        | CPU, PCIe, SATA |
| Ports & interfaces                            |                                                                                   | Weight & dimensions                    |                 |
| Motherboard power connector *                 | 20+4 pin ATX                                                                      | Width                                  | 150 mm          |
| Number of SATA power connectors               | 6                                                                                 | Depth                                  | 190 mm          |
| Peripheral (Molex) power connectors (4-pin) * | 2                                                                                 | Height                                 | 86 mm           |
|                                               |                                                                                   | Logistics data                         |                 |
|                                               |                                                                                   | Harmonized System (HS) code            | 84733020        |



4713224523823

### **Catalog Object Cloud**



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.