



HP 744 Matte Black/Chromatic Red DesignJet Printhead

Brand : HP

Product code: F9J88A

Product name : 744 Matte Black/Chromatic Red DesignJet Printhead



- Ideal for both graphics and technical applications.
 - Printhead
- 744 Matte Black/Chromatic Red DesignJet Printhead

HP 744 Matte Black/Chromatic Red DesignJet Printhead:

Ideal for both graphics and technical applications.

It's easy to produce a wide range of eye-catching graphics and technical applications with the reliable, hassle-free performance of user-replaceable HP 744 DesignJet Printheads.

HP 744 Matte Black/Chromatic Red DesignJet Printhead. Compatibility: HP DesignJet Z2600 PostScript Printer, HP DesignJet Z5600 PostScript Printer, Print technology: Thermal inkjet, Printing colours: Black. Width: 28 mm, Depth: 143 mm, Height: 132 mm. Package width: 28 mm, Package depth: 143 mm, Package height: 132 mm. Master (outer) cases per pallet: 80 pc(s), Products per pallet: 1920 pc(s), Layers per pallet: 8 pc(s). Pallet dimensions (W x D x H): 1016 x 1219 x 1318 mm, Pallet dimensions (W x D x H) (imperial): 1016 x 1218.9 x 1318 mm (40 x 48 x 51.9"), Pallet weight (imperial): 255.7 kg (563.7 lbs)



Performance		Logistics data	
Compatibility *	HP DesignJet Z2600 PostScript Printer, HP DesignJet Z5600 PostScript Printer	Master (outer) cases per pallet	80 pc(s)
Print technology	Thermal inkjet	Pallet dimensions (W x D x H)	1016 x 1219 x 1318 mm
Printing colours	Black	Products per pallet	1920 pc(s)
Country of origin	Singapore	Layers per pallet	8 pc(s)
Weight & dimensions		Pallet dimensions (W x D x H) (imperial)	1016 x 1218.9 x 1318 mm (40 x 48 x 51.9")
Width	28 mm	Pallet weight (imperial)	255.7 kg (563.7 lbs)
Depth	143 mm	Pallet gross weight	255.7 kg
Height	132 mm	Products per master (outer) case	24 pc(s)
Weight	80 g	Master (outer) case gross weight	2.95 kg
Packaging data		Quantity per pack	1 pc(s)
Package width	28 mm	Technical details	
Package depth	143 mm	Box contents	Printhead
Package height	132 mm	Total carbon footprint (kg of CO2e)	3.9
Package weight	110 g	Master (outer) cases per pallet layer	10 pc(s)
Operational conditions		Other features	
Operating temperature (T-T)	15 - 35 °C	UNSPSC-code	44103105
Operating relative humidity (H-H)	20 - 80%		
Storage temperature (T-T)	15 - 35 °C		



0725184104510



725184104510

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.