

DIGITUS Industrial mini GBIC (SFP) Module, 1.25 Gbps, 0.55km

DN-81010

EAN 4016032307570



1.25 Gbps SFP Module, Multimode, Industrial ver. LC Duplex Connector, 850nm, up to 550m

The DIGITUS® mini GBIC (SFP) transceiver modules offer highest quality and reliability. Whether from switch to switch, converter to switch, converter to converter or any else application: The wide product range of DIGITUS® modules makes possible a flexible usage of the fiber technology. The conformity to the MSA (Multi Source Agreement) standard ensures a compatibility to third party manufacturers.

The plug and play fiber connection

- Mini GBIC SFP (Small Form Factor Pluggable) module
- Compatible with the following manufacturers: Allied Telesis, Allnet, Avaya, CISCO, D-Link, Edimax, FINISAR, FORCE 10, Gigamon, Intellinet, KTI Networks, Level One, PLANET, Tenda, TP-Link, TRENDnet, Mikrotik, ENTERASYS, RIVERSTONE, Unifi, Ubiquiti, ZyXEL, ZTE
- High quality and excellent reliability
- 1.25 Gbps Maximum Data Rate
- Compliant to IEEE 802.3z Gigabit Standard
- Class 1 laser product compliant with EN 60825-1
- Easy plug-and-play installation
- MSA (Multi Source Agreement) compliant

- Hot pluggable
- Connector: 1x LC Duplex
- 1000Base-SX - For Short Haul
- Wavelength: 850nm
- Transmission power: minimum -8 dBm, maximum -3 dBm
- Sensitivity Receiving Power: Minimum -20 dBm
- For a Distance of up to 0.55km
- Suitable for 50/125µm and 62.5/125µm multimode fiber cables
- Safe fast-locking mechanism
- 3.3V power supply
- Operating temperature: -40 °C - +85 °C
- Mode: Multimode
- Connector: LC
- Distance (km): 0.5
- Wavelength: 850 nm
- DDM Support: no
- Broadcasting Mode: Unidirectional
- Manufacturer compatibility: Universal (MSA), Cisco
- Ethernet speed: Fast Ethernet


Package contents

- SFP module

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	240	8.50	50.00	29.00	54.50	79,025.00
Packaging Unit Inside	30	1.06	7.00	20.00	30.00	4,200.00
Packaging Unit Single	1	0.04	10.00	7.00	2.00	140.00
Net single without Packaging	1	0.00	0.00	0.00	0.00	0.00

More images:



SFP Modules							
Product Number	DOM Code	Speed	Distance	Connector	Wavelength	Operating Temperature	Industrial Version
Plastic SFP							
DM-40101	4010000000000	10 Gbps	2 km	LC Duplex	1310nm	0 to 70 °C	✓
DM-40102	4010000000002	10 Gbps	2 km	LC Duplex	1550nm	0 to 70 °C	✓
DM-40104	4010000000010	10 Gbps	2 km	LC Duplex	1310nm	0 to 70 °C	✓
Plastic SFP							
DM-40105	4010000000011	10 Gbps	2 km	LC Duplex	1310nm	0 to 70 °C	✓
DM-40106	4010000000012	10 Gbps	2 km	LC Duplex	1550nm	0 to 70 °C	✓
DM-40107	4010000000013	10 Gbps	2 km	LC Duplex	1310nm	0 to 70 °C	✓
DM-40108	4010000000014	10 Gbps	2 km	LC Duplex	1550nm	0 to 70 °C	✓
DM-40109	4010000000015	10 Gbps	2 km	LC Duplex	1310nm	0 to 70 °C	✓
DM-40110	4010000000016	10 Gbps	2 km	LC Duplex	1550nm	0 to 70 °C	✓
Plastic SFP							
DM-40111	4010000000017	10 Gbps	2 km	LC Duplex	1310nm	0 to 70 °C	✓
DM-40112	4010000000018	10 Gbps	2 km	LC Duplex	1550nm	0 to 70 °C	✓
DM-40113	4010000000019	10 Gbps	2 km	LC Duplex	1310nm	0 to 70 °C	✓
DM-40114	4010000000020	10 Gbps	2 km	LC Duplex	1550nm	0 to 70 °C	✓
DM-40115	4010000000021	10 Gbps	2 km	LC Duplex	1310nm	0 to 70 °C	✓
DM-40116	4010000000022	10 Gbps	2 km	LC Duplex	1550nm	0 to 70 °C	✓
DM-40117	4010000000023	10 Gbps	2 km	LC Duplex	1310nm	0 to 70 °C	✓
DM-40118	4010000000024	10 Gbps	2 km	LC Duplex	1550nm	0 to 70 °C	✓
DM-40119	4010000000025	10 Gbps	2 km	LC Duplex	1310nm	0 to 70 °C	✓
DM-40120	4010000000026	10 Gbps	2 km	LC Duplex	1550nm	0 to 70 °C	✓