



Acer Large Venue PL6520 Large venue projector 6000 ANSI lumens DLP 1080p (1920x1080) White

Brand : Acer

Product family: Large Venue

Product code: MR.JXH11.001

Product name : PL6520

Acer Large Venue PL6520. Projector brightness: 6000 ANSI lumens, Projection technology: DLP, Projector native resolution: 1080p (1920x1080). Light source type: Laser, Service life of light source: 20000 h, Service life of light source (economic mode): 30000 h. Focus: Manual, Focal length range: 17.63 - 27.90 mm, Aperture range (F-F): 2.3 - 3. Serial interface type: RS-232, HDMI version: 1.4b/2.0. Noise level: 33 dB, Noise level (economic mode): 27 dB



Projector		Ports & interfaces	
Supported aspect ratios	4:3	Audio (L/R) out	1
Projector brightness *	6000 ANSI lumens	Serial interface type *	RS-232
Projection technology *	DLP	HDMI ports quantity *	2
Projector native resolution *	1080p (1920x1080)	Network	
Contrast ratio (typical) *	50000:1	Ethernet LAN *	✓
Native aspect ratio *	16:9	Ethernet LAN (RJ-45) ports	1
Keystone correction, horizontal	+/- 30°	Storage	
Keystone correction, vertical	+/- 30°	Card reader integrated *	✗
Horizontal synchronization (min)	15 kHz	Features	
Horizontal synchronization (max)	100 kHz	Noise level (economic mode)	27 dB
Vertical synchronization (min)	24 kHz	Noise level *	33 dB
Vertical synchronization (max)	120 kHz	Multimedia	
Light source		Built-in speaker(s) *	✓
Light source type *	Laser	RMS rated power	30 W
Service life of light source *	20000 h	Number of built-in speakers	2
Service life of light source (economic mode)	30000 h	Design	
Lens system		Product type *	Large venue projector
Focus *	Manual	Product colour *	White
Focal length range	17.63 - 27.90 mm	Cable lock slot	✓
Aperture range (F-F)	2.3 - 3	Cable lock slot type	Kensington
Zoom type	Manual	Display	
Zoom ratio	1.7:1	Built-in display *	✗
Throw ratio	1.2 - 2.04	Power	
Video		Power source *	AC
Full HD *	✓	Power consumption (typical) *	245 W
Ports & interfaces		Power consumption (standby) *	0.5 W
HDMI version	1.4b/2.0	AC input voltage	100 - 240 V
Operational conditions			
		Operating temperature (T-T)	0 - 40 °C
Weight & dimensions			
		Width	374 mm
		Depth	265 mm
		Height	108 mm
		Weight *	4.5 kg



4711474116215

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 02-MAY-2026. Prints or copies of Information are only valid on the printed Publication date