



Canon imageFORMULA R30 Driverless Desktop Document Scanner

Brand : Canon

Product family:
imageFORMULA

Product code: 6051C003

Product name : Canon
imageFORMULA R30 Driverless
Desktop Document Scanner

A4, 600 x 600 dpi, CIS, LED RGB, 220 - 240 V CA (50/60 Hz), 3 kg

[Canon imageFORMULA R30 Driverless Desktop Document Scanner:](#)

Make scanning easier for everyone with a device designed for simplicity

Transform scanning processes with the user-friendly imageFORMULA R30. Simply connect your PC or laptop to the scanner and start scanning - its that easy! No need to install any drivers or software. The R30 makes the ideal easy solution for a small business, or a shared office space where a scanner device needs to be accessed by various people.

Canon imageFORMULA R30 Driverless Desktop Document Scanner. Maximum scan size: 216 x 356 mm, Optical scanning resolution: 600 x 600 DPI. Scanner type: ADF + Sheet-fed scanner, Product colour: White. Sensor type: CIS, Light source: RGB LED, Scan file formats: BMP, JPEG, PDF, PNG, PPTX, TIFF. Maximum ISO A-series paper size: A4, Scanning media types supported: Plastic Card, Media thickness (min): 0.04 mm. Power supply type: AC, Power consumption (typical): 10 W, Power consumption (off): 0.1 W



Scanning		Ports & interfaces	
Maximum scan size *	216 x 356 mm	USB port *	✓
Optical scanning resolution *	600 x 600 DPI	USB version	2.0
Colour scanning	✓	Power	
Duplex scanning *	✓	Power supply type *	AC
Design		Power consumption (typical)	10 W
Scanner type *	ADF + Sheet-fed scanner	Power consumption (off)	0.1 W
Product colour *	White	AC input frequency	50/60 Hz
Built-in display *	✗	Input voltage	220 - 240 V
Performance		Weight & dimensions	
Sensor type *	CIS	Width	293 mm
Light source	RGB LED	Depth	600 mm
Scan file formats	BMP, JPEG, PDF, PNG, PPTX, TIFF	Height	382 mm
Paper handling		Weight	3 kg
Scanning media types supported	Plastic Card	Folded width	29.3 cm
Maximum ISO A-series paper size *	A4	Folded depth	25.1 cm
Media thickness (min)	0.04 mm	Folded height	24.5 cm
Card thickness (max)	1.4 mm	Packaging data	
Maximum scan width	21.6 cm	Quantity per pack	1 pc(s)
Maximum scan length	35.6 cm	Operational conditions	
		Operating temperature (T-T)	10 - 32.5 °C
		Operating relative humidity (H-H)	20 - 80%



4528472111513

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.