



APC Smart-UPS RT 1000VA 230V - Marine

Brand : APC

Product code: SURT1000XLIM

Product name : APC Smart-UPS RT 1000VA 230V - Marine




- <a>Replacement battery (1) is available
APC Smart-UPS RT 1000VA 230V - Marine

APC Smart-UPS RT 1000VA 230V - Marine:

High availability, ruggedized power protection for shipboard and other transportation applications.
APC Smart-UPS RT 1000VA 230V - Marine. Output power capacity: 1 kVA, Output power: 700 W, Input operation voltage (min): 100 V. AC outlet types: C13 coupler, AC outlets quantity: 8 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery recharge time: 3 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Compliance certificates: RoHS, Certification: CE, DNV, EN 50091-1, EN 50091-2, EN 55022 Cl. A, EN 60950, EN 61000-3-2.

Features		Design	
Output power capacity *	1 kVA	Cable length	2.5 m
Output power *	700 W	Product colour *	Black
Input operation voltage (min) *	100 V	LED indicators	✓
Input operation voltage (max) *	280 V	Operational conditions	
Input frequency *	50/60 Hz	Operating temperature (T-T)	0 - 55 °C
Output operation voltage (min)	220 V	Storage temperature (T-T)	-20 - 50 °C
Output operation voltage (max)	240 V	Operating relative humidity (H-H)	0 - 95%
Surge energy rating	420 J	Storage relative humidity (H-H)	0 - 95%
Efficiency	88%	Operating altitude	0 - 3000 m
Crest factor	3:1	Non-operating altitude	0 - 15000 m
Emergency Power Off (EPO)	✓	Certificates	
Output voltage Total Harmonic Distortion (THD)	3%	Compliance certificates	RoHS
Noise level	55 dB	Certification	CE, DNV, EN 50091-1, EN 50091-2, EN 55022 Cl. A, EN 60950, EN 61000-3-2.
Ports & interfaces		Weight & dimensions	
AC outlet types	C13 coupler	Width	85 mm
AC outlets quantity	8 AC outlet(s)	Depth	483 mm
Number of output IEC jumpers	2	Height	432 mm
RS-232 ports	1	Weight	23 kg
Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Package weight	27.8 kg
Battery recharge time	3 h	Logistics data	
Design		Harmonized System (HS) code	85078000
Form factor *	Rackmount	Other features	
Rack capacity	2U	Dimensions (WxDxH)	85 x 483 x 432 mm
		Nominal output voltage	230 V
		Nominal input voltage	230 V
		Package dimensions (WxDxH)	630 x 594 x 286 mm



0731304283515



731304283515

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.