



APC SMT1500C uninterruptible power supply (UPS) Line-Interactive 1.44 kVA 1000 W 8 AC outlet(s)

Brand : APC

Product code: SMT1500C

Product name : SMT1500C

Smart-UPS 1500VA, LCD, 120V with SmartConnect

APC SMT1500C. UPS topology: Line-Interactive, Output power capacity: 1.44 kVA, Output power: 1000 W. AC outlet types: NEMA 5-15R, AC outlets quantity: 8 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 5 year(s), Battery recharge time: 3 h. Form factor: Tower, Product colour: Black, Cable length: 1.83 m. Compliance certificates: RoHS, Certification: REACH




Features		Battery	
UPS topology *	Line-Interactive	Automatic battery test	✓
Output power capacity *	1.44 kVA	Cold start	✓
Output power *	1000 W	Design	
Waveform *	Sine	Form factor *	Tower
Input operation voltage (min) *	75 V	Cable length	1.83 m
Input operation voltage (max) *	154 V	Product colour *	Black
Input frequency *	50/60 Hz	Display type	LCD
Output operation voltage (min)	110 V	LED indicators	Status
Output operation voltage (max)	127 V	Operational conditions	
Automatic Voltage Regulation (AVR)	✓	Operating temperature (T-T)	0 - 40 °C
Surge energy rating	680 J	Storage temperature (T-T)	-15 - 45 °C
Response time	10 ms	Operating relative humidity (H-H)	0 - 95%
EMI/RFI noise filtering	✓	Storage relative humidity (H-H)	0 - 95%
Noise level	45 dB	Operating altitude	0 - 3000 m
Power protection features	Short circuit	Non-operating altitude	0 - 15000 m
Audible alarm(s)	✓	Certificates	
Web-based management	✓	Compliance certificates	RoHS
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm	Certification	REACH
Auto-restart	✓	Packaging content	
Ports & interfaces		Cables included	RS-232, USB cable
AC outlet types	NEMA 5-15R	Sustainability	
AC outlets quantity	8 AC outlet(s)	Sustainability certificates	ENERGY STAR
USB port	✓	Weight & dimensions	
Serial interface	✓	Width	171 mm
SmartSlot	✓	Depth	439 mm
Battery		Height	219 mm
Battery technology	Sealed Lead Acid (VRLA)	Weight	24.6 kg
Number of batteries supported	1		

Battery		Packaging data	
Battery life (max)	5 year(s)	Resource CD	✓
Battery recharge time	3 h	Software CD	✓
Hot-swap battery	✓	Package width	330 mm
		Package depth	590 mm
		Package height	330 mm
		Package weight	27.2 kg
		Logistics data	
		Harmonized System (HS) code	85078000



0731304322795



731304322795

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.