



Dahua Technology DH-XVR5216A-4KL-I3 digital video recorder (DVR) Black



Brand : Dahua Technology

Product code: DH-XVR5216A-4KL-I3

Product name : DH-XVR5216A-4KL-I3

- H.265+/H.265 dual-stream video compression
 - Supports Full-channel AI-Coding
 - Supports HDCVI/AHD/TVI/CVBS/IP video inputs
 - Max 32 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth
 - Up to 8 channels video stream (analog channel) Perimeter Protection
 - Up to 16 channels video stream (analog channel) SMD Plus
 - Up to 2 channels video stream (analog channel) human face recognition
 - IoT & POS functionalities
- H.265+/H.265, 16 Channels, 1U, 12 VDC, 5 A, 1.8 kg, black

Dahua Technology DH-XVR5216A-4KL-I3 digital video recorder (DVR) Black:

16 Channels Penta-brid 4K-N/5MP 1U 2HDDs WizSense Digital Video Recorder

Performance		Ports & interfaces	
Maximum video resolution	3840 x 2160 pixels	RS-485 ports	1
Video compression formats	H.264, H.264+, H.265, H.265+	Network	
Audio formats supported	G.711 A-law, G.711 μ -law, PCM	Ethernet LAN	✓
Video capturing speed	30 fps	Ethernet interface type	Fast Ethernet, Gigabit Ethernet
Video capturing speed (PAL)	25 fps	Ethernet LAN (RJ-45) ports	1
Video capturing speed (NTSC)	30 fps	Supported network protocols	HTTP; HTTPS; TCP / IP; IPv4; RTSP; UDP; SMTP; NTP; DHCP; DNS; DDNS; P2P
Channels quantity	16 channels	Power	
Product colour *	Black	Power supply type	DC
Analog signal format system	NTSC, PAL	DC voltage	12 V
Operating system installed	Embedded LINUX	Weight & dimensions	
Bit rate	64 Kbit/s	Width	375 mm
Rack capacity	1U	Depth	289.4 mm
Certification	CE: CE-LVD: EN 60950-1/IEC 60950-1 CE-EMC: EN 61000-3-2, EN 61000-3-3, EN 55032, EN 50130, EN 55024 FCC: Part 15 Subpart B	Height	53 mm
		Weight	1.8 kg
Ports & interfaces		Packaging data	
HDMI ports quantity	1	Package width	433 mm
VGA (D-Sub) output ports	1	Package depth	141 mm
USB 2.0 ports quantity	1	Package height	366 mm
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1	Package weight	2.98 kg
Video RCA outputs	1	Operational conditions	
		Operating temperature (T-T)	-10 - 55 °C
		Operating relative humidity (H-H)	10 - 90%



6923172539755

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.