

Allied Telesis GS950/10PS Managed Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Green, Grey

Brand : Allied Telesis

Product code: AT-GS950/10PS

Product name : GS950/10PS

WebSmart switch 10 port PoE+ GigT 10 POE capable + 2 SFP Combo ports

Allied Telesis GS950/10PS Managed Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Green, Grey:

The Allied Telesis GS950/10PS Gigabit Ethernet WebSmart switch features two Gigabit ports, two SFP combo ports, and eight PoE+ ports delivering up to 30 Watts per port to support video surveillance and security cameras, wireless access points, IP phones and other PoE powered devices. The PoE option eliminates the need for power rewiring and minimizes the clutter of power supplies and adapters in awkward places. Thanks to its compact size, the AT-GS950/10PS is ideal for wiring-constrained and smaller environments such as micro branch offices, classrooms, cafes, and smaller retail stores.

Management features		Security	
Switch type *	Managed	DHCP features	DHCP client, DHCP server
Quality of Service (QoS) support	✓	IGMP snooping	✓
Web-based management	✓	MAC address filtering	✓
MIB support	RFC 1213 MIB-II, RFC 1215 TRAP MIB, RFC 1493 Bridge MIB, RFC 2863, RFC 1643, RFC 2618 RMON, RFC 2674 IEEE 802.1Q, RFC 2096 IP	Multicast features	
		Multicast support	✓
Ports & interfaces		Design	
Basic switching RJ-45 Ethernet ports quantity *	8	Product colour	Green, Grey
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Performance	
Gigabit Ethernet (copper) ports quantity	10	Internal memory	64 MB
Combo SFP ports quantity	2	Flash memory	16 MB
Fiber ports quantity	2	Power	
Fiber optic connector	SFP	AC input voltage	100 - 240 V
Console port	RJ-45	Power consumption (typical)	13.58 W
Power connector	DC-in jack	Power over Ethernet (PoE)	
Network		Power over Ethernet (PoE) *	✓
Networking standards *	IEEE 802.1D, IEEE 802.1p, IEEE 802.1s, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Power over Ethernet plus (PoE+) ports quantity	8
10G support *	✗	Total Power over Ethernet (PoE) budget	75 W
Copper ethernet cabling technology	10BASE-T, 100BASE-T, 1000BASE-T	Operational conditions	
Port mirroring	✓	Operating temperature (T-T)	0 - 40 °C
Full duplex	✓	Storage temperature (T-T)	-25 - 70 °C
Flow control support	✓	Operating relative humidity (H-H)	5 - 90%
Rate limiting	✓	Storage relative humidity (H-H)	5 - 95%
VLAN support	✓	Operating altitude	0 - 3048 m
Optical fiber		Weight & dimensions	
Fiber ethernet cabling technology	100BASE-FX, 1000BASE-LX, 1000BASE-SX	Width	330 mm
Fiber type	Multi-mode	Depth	200 mm
		Height	44 mm
		Weight	1.9 kg
Data transmission		Certificates	
Switching capacity *	20 Gbit/s	Certification	RoHS Eu-RoHS China RoHS WEEE
Throughput	14.88 Mpps	Logistics data	
MAC address table *	8000 entries	Harmonized System (HS) code	85176990



0767035219158



767035219158

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.