



TP-Link XX530V wireless router Gigabit Ethernet Dual-band (2.4 GHz / 5 GHz) Black

Brand : TP-Link

Product code: XX530V

Product name : XX530V

AX3000 Dual Band WiFi 6 GPON Router

TP-Link XX530V. Wi-Fi band: Dual-band (2.4 GHz / 5 GHz), Top Wi-Fi standard: Wi-Fi 6 (802.11ax), WLAN data transfer rate (max): 2402 Mbit/s. Ethernet LAN interface type: Gigabit Ethernet, Ethernet LAN data rates: 1000,100 Mbit/s, VPN server: PPTP VPN, IPSec VPN , OpenVPN. Security algorithms: WPA, WPA2, WPA3. Product type: Tabletop router, Product colour: Black. Antenna design: External, Transmit power: <20 dBm (2.4 GHz); <23 dBm (5 GHz)

WAN connection		Security	
Ethernet WAN *	✓	Security algorithms	WPA, WPA2, WPA3
DSL WAN *	✗	Firewall	✓
SIM card slot *	✗	Guest access	✓
3G/4G USB modem compatibility *	✗	Schedule access	✓
Wireless LAN features		Parental control	✓
Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)	Filtering	✓
Top Wi-Fi standard *	Wi-Fi 6 (802.11ax)	MAC address filtering	✓
WLAN data transfer rate (max) *	2402 Mbit/s	IP address filtering	✓
Wi-Fi standards	802.11a, 802.11b, 802.11ad,	URL filtering	✓
	802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	IGMP snooping	✓
Network		DMZ support	✓
Ethernet LAN *	✓	Network address translation (NAT)	✓
Ethernet LAN interface type *	Gigabit Ethernet	Protocols	
Ethernet LAN data rates	1000,100 Mbit/s	DHCP client	✓
Port forwarding	✓	DHCP server	✓
Port triggering	✓	Universal Plug and Play (UPnP)	✓
Dynamic DNS (DDNS)	✓	Design	
SSID-based VLAN assignment	✓	Product colour	Black
VPN server	PPTP VPN, IPSec VPN , OpenVPN	Product type *	Tabletop router
PPPoE/PPTP/L2TP pass-through	✓	Antenna	
Ports & interfaces		Antenna design *	External
Ethernet LAN (RJ-45) ports *	4	Antennas quantity	2
USB port *	✓	Transmit power	<20 dBm (2.4 GHz); <23 dBm (5 GHz)
USB 2.0 ports quantity	1	Power	
SC/APC GPON ports quantity	1	Power source type *	AC
Management features		Output voltage	12 V
Wi-Fi Multimedia (WMM)/(WME)	✓	Output current	1.5 A
Quality of Service (QoS) support	✓	Operational conditions	
Reset button	✓	Operating temperature (T-T)	0 - 40 °C
WPS push button	✓	Storage temperature (T-T)	-40 - 60 °C
Intelligent Mesh technology	✓	Operating relative humidity (H-H)	10 - 90%
Traffic statistics	✓	Storage relative humidity (H-H)	5 - 90%

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.