



TP-Link EB210 PRO wireless router 2.5 Gigabit Ethernet Dual-band (2.4 GHz / 5 GHz) Black



Brand : TP-Link

Product code: EB210 PRO

Product name : EB210 PRO

- BE3600 Dual-Band Wi-Fi: 2880 Mbps (5 GHz, EHT160) + 688 Mbps (2.4 GHz, EHT40)
- Multi-Gig Internet Connections: 1× 2.5GE WAN port, 1× 2.5GE LAN port, and 3× GE LAN ports provide ultra-fast speeds and flexible internet access.§
- Next-Gen Wi-Fi Technology: Enjoy extreme Wi-Fi performance in network speed, efficiency, and capacity with cutting-edge technologies.‡
- EasyMesh-Compatible◇: Create a smart mesh network with seamless coverage and greater flexibility.
- Remote Management: TR-069 and TR-369 protocols and TAUC (TP-Link Agent Unified Cloud) are supported.

BE3600 Dual-Band Wi-Fi 7 Router

WAN connection		Management features	
Ethernet WAN *	✓	WPS push button	✓
DSL WAN *	✗	Cloud-managed	✓
SIM card slot *	✗	Security	
3G/4G USB modem compatibility *	✗	Security algorithms	WPA, WPA2, WPA3-Personal
WAN connection type	RJ-45	Firewall	✓
Wireless LAN features		Firewall security	DoS, SPI Firewall, IP & MAC Address Binding
Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)	Design	
Top Wi-Fi standard *	Wi-Fi 7 (802.11be)	Product colour	Black
WLAN data transfer rate (max) *	3568 Mbit/s	Product type *	Tabletop router
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax), Wi-Fi 6E (802.11ax), Wi-Fi 7 (802.11be)	Certificates	
WLAN data transfer rate (first band)	688 Mbit/s	Certification	CE
WLAN data transfer rate (second band)	2880 Mbit/s	Packaging content	
Network		Cables included	LAN (RJ-45)
Ethernet LAN *	✓	AC adapter included	✓
Ethernet LAN interface type *	2.5 Gigabit Ethernet	Quick installation guide	✓
VPN support	PPTP, OpenVPN, IPSec	Antenna	
Mobile network		Antenna design *	External
Mobile network generation	Not supported	Power	
Ports & interfaces		Power source type *	DC
Ethernet LAN (RJ-45) ports *	5	Operational conditions	
USB port *	✓	Operating temperature (T-T)	0 - 40 °C
Management features		Storage temperature (T-T)	-40 - 60 °C
Quality of Service (QoS) support	✓	Operating relative humidity (H-H)	10 - 90%
Reset button	✓	Storage relative humidity (H-H)	5 - 90%
		Weight & dimensions	
		Width	268.6 mm
		Depth	153 mm
		Height	47.6 mm

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.