

## Epson WorkForce DS-1730 Flatbed & ADF scanner 1200 x 1200 DPI A4 Black, White

**Brand :** Epson

**Product family:** WorkForce

**Product code:** B11B273401

**Product name :** DS-1730



WorkForce DS-1730 compact flatbed scanner for small businesses and home offices.

Epson WorkForce DS-1730 Flatbed & ADF scanner 1200 x 1200 DPI A4 Black, White:

The DS-1730 is the perfect business solution for users seeking a flatbed scanner that balances affordability with impressive performance. This scanner delivers reliable and consistent quality, meeting professional standards, without exceeding budget constraints. With a simple, unobtrusive design and compact footprint, the DS-1730 empowers users to achieve professional results.

Epson WorkForce DS-1730. Maximum scan size: 215.9 x 297 mm, Optical scanning resolution: 1200 x 1200 DPI, Input colour depth: 30 bit. Scanner type: Flatbed & ADF scanner, Product colour: Black, White. Sensor type: CIS, Daily duty cycle (max): 3000 pages, Light source: RGB LED. Standard input capacity: 60 sheets. Maximum ISO A-series paper size: A4, Scanning media types supported: Business Card, Plastic Card, ISO A-series sizes (A0...A9): A4, A5, A6



| Scanning                          |                             | Ports & interfaces                  |                                                           |
|-----------------------------------|-----------------------------|-------------------------------------|-----------------------------------------------------------|
| Maximum scan size *               | 215.9 x 297 mm              | USB port *                          | ✓                                                         |
| Optical scanning resolution *     | 1200 x 1200 DPI             | USB version                         | 2.0                                                       |
| Duplex scanning *                 | ✓                           | <b>Power</b>                        |                                                           |
| Input colour depth                | 30 bit                      | Power supply type *                 | AC                                                        |
| Output colour depth               | 24 bit                      | Power consumption (typical)         | 9 W                                                       |
| Input greyscale depth             | 10 bit                      | Sleep mode                          | ✓                                                         |
| Output greyscale depth            | 8 bit                       | Input voltage                       | 100 - 240 V                                               |
| Design                            |                             | Weight & dimensions                 |                                                           |
| Scanner type *                    | Flatbed & ADF scanner       | Width                               | 425 mm                                                    |
| Product colour *                  | Black, White                | Depth                               | 351 mm                                                    |
| Built-in display *                | ✗                           | Height                              | 135 mm                                                    |
| Performance                       |                             | Weight                              | 4.82 kg                                                   |
| Sensor type *                     | CIS                         | <b>Packaging data</b>               |                                                           |
| Light source                      | RGB LED                     | Quantity per pack                   | 1 pc(s)                                                   |
| Scan file formats                 | BMP, JPEG, PDF, PNG, TIFF   | <b>Packaging content</b>            |                                                           |
| Daily duty cycle (max) *          | 3000 pages                  | Cables included                     | AC, USB                                                   |
| Scan drivers                      | ISIS, SANE, TWAIN, WIA      | <b>System requirements</b>          |                                                           |
| Input capacity                    |                             | Windows operating systems supported | Windows 10, Windows 11, Windows 7, Windows 8, Windows 8.1 |
| Standard input capacity           | 60 sheets                   |                                     |                                                           |
| Paper handling                    |                             |                                     |                                                           |
| Scanning media types supported    | Business Card, Plastic Card |                                     |                                                           |
| Maximum ISO A-series paper size * | A4                          |                                     |                                                           |
| ISO A-series sizes (A0...A9)      | A4, A5, A6                  |                                     |                                                           |
| ISO B-series sizes (B0...B9)      | B5, B6                      |                                     |                                                           |
| Letter                            | ✓                           |                                     |                                                           |
| Legal                             | ✓                           |                                     |                                                           |

| Paper handling          |               | System requirements                |                                                                                                                                                                                                                                                                                                                                                                                            |
|-------------------------|---------------|------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Paper tray media weight | 50 - 120 g/m² |                                    | Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.2 Jaguar, Mac OS X 10.3 Panther, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.7.5 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura, Mac OS X 14.0 Sonoma, Mac OS X 15.0 Sequoia |
|                         |               | Mac operating systems supported    |                                                                                                                                                                                                                                                                                                                                                                                            |
|                         |               | Server operating systems supported | Windows Server 2008, Windows Server 2012 x64, Windows Server 2016, Windows Server 2022                                                                                                                                                                                                                                                                                                     |
| Operational conditions  |               |                                    |                                                                                                                                                                                                                                                                                                                                                                                            |
|                         |               | Storage temperature (T-T)          | -25 - 60 °C                                                                                                                                                                                                                                                                                                                                                                                |
|                         |               | Operating relative humidity (H-H)  | 15 - 60%                                                                                                                                                                                                                                                                                                                                                                                   |
|                         |               | Storage relative humidity (H-H)    | 15 - 85%                                                                                                                                                                                                                                                                                                                                                                                   |



8715946737560



8715946737577

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.