



APC Smart-UPS X SMX2200HVNC - 2200VA, 8x C13 + 2x C19 outlet, USB, expandable runtime, short depth, NMC

Brand : APC

Product code: SMX2200HVNC

Product name : APC Smart-UPS X SMX2200HVNC - 2200VA, 8x C13 + 2x C19 outlet, USB, expandable runtime, short depth, NMC

APC Smart-UPS X SMX2200HVNC - 2200VA, 8x C13 + 2x C19 outlet, USB, expandable runtime, short depth, NMC

APC Smart-UPS X SMX2200HVNC - 2200VA, 8x C13 + 2x C19 outlet, USB, expandable runtime, short depth, NMC. UPS topology: Line-Interactive, Output power capacity: 2.2 kVA, Output power: 1980 W. AC outlet types: C13 coupler, C19 coupler, C20 coupler, Power plug: C20 coupler, AC outlets quantity: 10 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 702 Ah, Battery recharge time: 3 h. Form factor: Rackmount/Tower, Product colour: Black, Rack capacity: 2U. Compliance certificates: RoHS, Certification: CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE



Features		Design	
UPS topology *	Line-Interactive	Form factor *	Rackmount/Tower
Output power capacity *	2.2 kVA	Rack capacity	2U
Output power *	1980 W	Cable length	2 m
Waveform *	Sine	Product colour *	Black
Input operation voltage (min) *	140 V	Display type	LED
Input operation voltage (max) *	280 V	LED indicators	✓
Input frequency *	50/60 Hz	Operational conditions	
Output operation voltage (min)	208 V	Operating temperature (T-T)	0 - 40 °C
Output operation voltage (max)	240 V	Storage temperature (T-T)	-15 - 45 °C
Output frequency	50/60 Hz	Operating relative humidity (H-H)	0 - 95%
Output frequency regulation	+/- 3 Hz	Storage relative humidity (H-H)	0 - 95%
Output voltage regulation	5%	Operating altitude	0 - 3000 m
Response time	10 ms	Non-operating altitude	0 - 15000 m
Emergency Power Off (EPO)	✓	Certificates	
EMI/RFI noise filtering	✓	Compliance certificates	RoHS
Noise level	55 dB	Certification	CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE
Surge protection	✓	Packaging content	
Audible alarm(s)	✓	Rack mount kit	✓
Web-based management	✓	Cables included	Input power cable, USB cable
Audible alarm modes	Battery replacement	Management card included	✓
Auto-restart	✓	Quick installation guide	✓
Ports & interfaces		Weight & dimensions	
AC outlet types	C13 coupler, C19 coupler, C20 coupler	Width	178 mm
Power plug	C20 coupler	Depth	483 mm
AC outlets quantity	10 AC outlet(s)	Height	432 mm
USB 2.0 ports quantity	1	Weight	38.6 kg
Ethernet LAN (RJ-45) ports	1	Packaging data	
SmartSlot	✓		
SmartConnect port	✗		

Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Resource CD	✓
Battery capacity	702 Ah	Package width	586 mm
Battery recharge time	3 h	Package depth	633 mm
Hot-swap battery	✓	Package height	330 mm
Automatic battery test	✓	Package weight	47.6 kg
Cold start	✓	Logistics data	
		Products per pallet	6 pc(s)
		Harmonized System (HS) code	85078000
		Total carbon footprint (kg of CO2e)	3234.06
		Other features	
		Output voltage	230 V



0731304327158



731304327158

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.